

ShurBond



ShurBond is a waterborne acrylic bonding agent.

Product Specifications:

Packaging:

40 lbs. (18.1 kg.) 5 Gallon Plastic Pail

8 lbs. (3.62) 1 Gallon plastic bottle

Coverage Rate:

Approximate coverage is 75-175 sq. ft. per gallon. The coverage will vary depending on the substrate, surface texture and application technique.

Color:

White viscous liquid

Storage:

Store in a cool, dry interior place. Keep from freezing, out of direct sunlight for long periods, and at no time expose to moisture, rain or snow. Storage temperature ranges between 40°F (4.4°C) and 95°F (35°C)

Clean up:

Clean tools and equipment with water immediately after use.

Shelf Life:

1 year

Uses:

ShurBond is applied over painted surfaces to improve adhesion of cementitious coatings. ShurBond evens surface absorption, allowing a uniform overlay. ShurBond may also be used to increase bond strength between cementitious products.



Features:

- Control
- Stability
- Economical

Benefits:

- Assists in controlling cracking and shrinkage
- Increases the freeze/thaw stability
- 1 part Shurbond to 3 parts potable water

March 2010

UltraKote Products, Inc.
327 South 27th Avenue, Phoenix, Arizona 85009
Phone: 800.224.2344 Fax: 602.272.6445

www.ultrakoteproducts.com

ShurBond™



Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose paint,

Mixing:

Shake vigorously before use. If ShurBond is to be used in a spray application it is recommended to consult with the UltraKote technical department for proper guidelines. For all other applications do not add water or dilute ShurBond unless otherwise specified by UltraKote technical representative.

Application:

ShurBond may be applied by roller, brush or spray equipment. Allow enough time for bonding agent to become tacky before applying overlay.

Curing / Drying:

Drying time will vary depending ambient temperature, humidity and thickness of application. Material will dry completely within 2 hours.

Limitations:

ShurBond should be applied when surface and ambient temperature are between 45°F and 110°F. Paint should be cured for 60 days before ShurBond is used.

Technical Data:



Precautions:

KEEP OUT OF THE REACH OF CHILDREN.
Not for internal consumption.
Do not apply in non-ventilated area.
Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes.
In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing.
If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.
For additional information refer to the Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN.
NOT FOR INTERNAL CONSUMPTION,
FOR INDUSTRIAL USE ONLY

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Information Guide conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc. or visit website at www.ultrakoteproducts.com.

March 20109

Ultra-
Kote Products, Inc.

327 South 27th Avenue, Phoenix, Arizona 85009
Phone: 800.224.2344 Fax: 602.272.6445

www.ultrakoteproducts.com