

3. HAZARDS IDENTIFICATION:

POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY.....: Inhalation; Skin Contact; Eye Contact; Ingestion.

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

ACUTE INHALATION.....: May cause respiratory tract irritation.

CHRONIC INHALATION.....: Pre-existing respiratory conditions may be aggravated by exposure. This product contains silicone dioxide (quartz) which has been listed as a suspected human carcinogen by OSHA, NTP, State of California and IRC.

ACUTE SKIN CONTACT.....: Substance, may cause slight skin irritation.

CHRONIC SKIN CONTACT.....: Pre-existing skin conditions may be aggravated by exposure.

ACUTE EYE CONTACT.....: May cause slight irritation.

CHRONIC EYE CONTACT.....: Not Determined.

ACUTE INGESTION.....: Irritating to mouth, throat and stomach.

CHRONIC INGESTION.....: Not Determined.

CARCINOGENICITY.....: This product contains silicone dioxide (quartz) which has been listed as a suspected human carcinogen by OSHA, NTP, State of California and IRC.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known.

Continued on page 3

4. FIRST AID MEASURES:

FIRST AID FOR EYES.....: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID FOR SKIN.....: Remove contaminated clothing and shoes. Wash affected area(s) thoroughly with soap and water. If irritation persists, seek medical attention.

FIRST AID FOR INHALATION...: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID FOR INGESTION: If swallowed, DO NOT induce vomiting. Give victim one glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victims head below hips to avoid aspiration of vomit into lungs.

NOTE TO PHYSICIAN.....: EYES: None.
SKIN: None.
INGESTION: None.
INHALATION: None.

5. FIRE FIGHTING MEASURES:

FLASH POINT:: N.A. Setaflash (ASTM D-3243, D-3278, D-3828)

FLAMMABLE LIMITS.....: UPPER EXPLOSIVE LIMIT (UEL)(%): Not established.
LOWER EXPLOSIVE LIMIT (LEL)(%): Not established.

AUTO-IGNITION TEMPERATURE:.....: Not Determined - DIN 51794

EXTINGUISHING MEDIA:.....: Dry Chemical; Carbon Dioxide; Foam; Water spray for large fires.

SPECIAL FIRE FIGHTING PROCEDURE..: None

6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES.: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbet/sweep cycle until the spill has dried up. Avoid run off to storm sewers or ditches which lead to waterways.

7. HANDLING AND STORAGE:

STORAGE TEMPERATURE (MIN/MAX).....: 40 °F / 100°F.

SHELF LIFE.....: 12 months at 77°F.

SPECIAL SENSITIVITY.....: Not Determined.

HANDLING/STORAGE PRECAUTIONS.....: None.

8. PERSONAL PROTECTION:

REQUIRED WORK/HYGIENE PROCEDURES.: None Established.

EYE PROTECTION REQUIREMENTS.....: OSHA 87.1Z safety glasses should be worn.

SKIN PROTECTION REQUIREMENTS.....: Chemical resistant gloves.

VENTILATION REQUIREMENTS.....: Allow for adequate natural ventilation when applying.

RESPIRATOR REQUIREMENTS.....: An OSHA dust and particulate mask should be worn during mixing and handling of this product in dry state.

ADDITIONAL PROTECTIVE MEASURES.....: None.

9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL FORM.....: Fine and gritty powder mixture.

COLOR.....: Gray.

ODOR.....: Odorless.

ODOR THRESHOLD.....: N.A.

MOLECULAR WEIGHT.....: Not Determined.

pH: 13.0 – 14.0 s.u. (When wet)

BOILING POINT.....: N.A.

MELTING/FREEZING POINT.....: N.A.

VISCOSITY.....: N.A.

SOLUBILITY IN WATER: Partially.

SPECIFIC GRAVITY: 2.33 g.cm³

BULK DENSITY.....: 90.0 lbs/ft³.

VAPOR PRESSURE: N.A..

VAPOR DENSITY: Is Heavier Than Air (Air = 1).

VOC BY WEIGHT: 0.0 g/liter.

10. STABILITY AND REACTIVITY:

STABILITY.....: Very stable, no known reactions under normal conditions and environments.

HAZARDOUS POLYMERIZATION...: Will Not Occur.

INCOMPATIBILITIES.....: Oxidizing Agents, strong bases or strong acids

INSTABILITY CONDITIONS.....: Not Determined.

DECOMPOSITION PRODUCTS.....: Not Determined

11. TOXICOLOGICAL INFORMATION:

ACUTE TOXICITY

ORAL LD50.....: Not Determined.

DERMAL LD50.....: Not Determined.

INHALATION LC50.....: Not Determined.

EYE EFFECTS.....: Not Determined.

SKIN EFFECTS.....: Not Determined.

SENSITIZATION.....: Not Determined.

OTHER ACUTE EFFECTS.....: Not Determined.

OTHER TOXICITY DATA.....: Not Determined.

12. ECOLOGICAL INFORMATION:

NO ECOLOGICAL INFORMATION AVAILABLE.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD.....: Waste must be disposed of in accordance with federal, state and local environmental control regulations.

14. TRANSPORTATION INFORMATION:

TECHNICAL SHIPPING NAME.....: Cement

FREIGHT CLASS BULK.....: Not Regulated

FREIGHT CLASS PACKAGE.....: None.

PRODUCT LABEL.....: None.

DOT (DOMESTIC SURFACE)

PROPER SHIPPING NAME.....: Cement.

HAZARD CLASS OR DIVISION: Not Regulated.

UN/NA NUMBER.: None.

PACKING GROUP: None.

DOT PRODUCT RQ lbs (kgs): None.

HAZARD LABEL(s): None.

HAZARD PLACARD(s).....: None.

14. TRANSPORTATION INFORMATION: (Continued)

IMO / IMDG CODE (OCEAN)

HAZARD CLASS DIVISION NUMBER.....: Non-Regulated

ICAO / IATA (AIR)

HAZARD CLASS DIVISION NUMBER.....: Non-Regulated

15. REGULATORY INFORMATION:

OSHA STATUS.....: Not Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

TSCA STATUS.....: This product contains no chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SARA TITLE III:

SECTION 302

EXTREMELY HAZARDOUS SUBSTANCES...: None

SECTION 311/312

HAZARD CATEGORIES.....: None

SECTION 313

TOXIC CHEMICALS.....: No SARA Section 313 components exist in this product.

RCRA STATUS.....: Not Regulated

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME	CAS NUMBER	CONCENTRATION	STATE CODE
Silica Quartz	14808-60-7	<75.0%	CA, MA

CALIFORNIA PROPOSITION 65

This product contains the chemicals listed above in the stated concentration, which the state of California has found to cause cancer, birth defects or other reproductive effects.

MASSACHUSETTS SUBSTANCE LIST (MSL)

Hazardous Substances and Extraordinarily Hazardous Substances on the MSL must be identified when present in products. This product contains the above listed chemicals or substances at a level which requires reporting under the statute.

Continued on page 7

16. OTHER INFORMATION:

HMIS RATINGS: Health Flammability Reactivity
 2* 0 1

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

*=Chronic Health Hazard

ULTRAKOTE method of hazard communication is comprised of Product Labels and Material Safety Data Sheets. HMIS ratings are provided by ULTRAKOTE as a customer service.

REASON FOR ISSUE.....: REVISION OF FORMAT

PREPARED BY.....: A.D.Skelhorn.

ISSUE DATE.....: 10/18/2006

SUPERSEDES DATE.....: 01/20/2005

MSDS NUMBER.: #####

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ULTRAKOTE. The data on this sheet relates only to the specific material designated herein. ULTRAKOTE assumes no legal responsibility for use or reliance upon this data.

Product Code: #####

Approval date: 10/18/2006