



UltraBond

Product Data Sheet

Description:

UltraBond is a waterborne acrylic bonding agent.

Uses:

UltraBond is applied over painted surfaces to improve adhesion of cementitious coatings. UltraBond evens surface absorption, allowing a uniform overlay. UltraBond may also be used to increase bond strength between cementitious products.

Color:

White liquid

Packaging:

1 gallon plastic bottle- 8 lbs.
(3.62 kg.)
5 gallon plastic pail- 40 lbs.
(18.1 kg.)

Coverage:

Approximate coverage is 75-175 sq. ft. per gallon (coverage will vary depending on substrate, surface texture and application technique).

Mixing:

Shake vigorously before use. If UltraBond is to be used in a spray application it is recommended to consult with the UltraKote technical department for proper guidelines. For all other applications do not add water or dilute UltraBond unless otherwise specified by UltraKote technical representative.

Limitations:

UltraBond should be applied when surface and ambient temperature are between 45°F and 110°F. Paint should be cured for 60 days before UltraBond is used.

Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Repair all cracks with UltraPatching Compound. If applying over a painted surface, test paint to make sure it is load bearing. Failure to correctly prepare the surface may result in product failure.

Application:

UltraBond may be applied by roller, brush or spray equipment. Allow enough time for bonding agent to become tacky before applying overlay.

Curing/Drying:

Drying time will vary depending ambient temperature, humidity and thickness of application. Material will dry completely

within 2 hours.

Storage/Shelf Life:

Product is good for one year when stored in a cool dry place and out of direct sunlight. Keep from freezing.

Clean Up:

Clean tools and equipment with water immediately after use.

UltraKote Products, Inc.

327 S. 27th Avenue
Phoenix, AZ 85009
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

UltraBond

Product Data Sheet

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the UltraBond Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272.5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc
