



# Admixture

## Product Data Sheet

---

### Description:

UltraKote Admix is a concentrated, waterborne acrylic polymer additive for use with cementitious materials.

### Uses:

UltraKote Admix, when diluted, is added to cementitious materials to reduce cracking and shrinking, while improving tensile, flexural and compressive strengths. When added to cementitious materials, UltraKote Admix will produce a polymer-modified cement that will increase freeze/thaw stability.

### Color:

White viscous liquid

### Packaging:

1-gallon plastic bottle- 8 lbs.  
(3.62 kg.)  
5-gallon plastic pail- 40 lbs.  
(18.1 kg.)

### Mixing:

Shake vigorously before use. In a clean pail, mix 1 part UltraKote Admix with 3 parts potable water. Reduce dilution ratio for greater polymer modification. Add this mix to any cementitious material that requires polymer modification.

### Limitations:

UltraKote Admix should be used with cementitious materials being applied between 45°F and 110°F.

### Surface Preparation:

When using UltraKote Admix with other products, surfaces must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Failure to correctly prepare the surface may result in product failure.

### Curing/Drying:

Drying time for modified cementitious materials will vary depending on ambient temperature, humidity and thickness of application. Use of UltraKote Admix may reduce open time of original cementitious products by 5-10%.

### Storage/Shelf Life:

Product is good for one year when stored in a cool dry place and out of direct sunlight. Keep from freezing.

### Clean Up:

Clean tools and equipment with water immediately after use.

---

### UltraKote Products, Inc.

327 S. 27th Avenue  
Phoenix, AZ 85009  
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

# UltraKote Admix

## Product Data Sheet

---

**Precautions:**

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

**First Aid:**

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the AdMixture Material Safety Data Sheet (MSDS).

**Disposal:**

Dispose of in accordance with local, state or federal regulations.

**Warning:**

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

**Spills:**

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

**Prop 65:**

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

**Technical Support:**

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc

---