



StuccoKote

Product Data Sheet

Description:

StuccoKote is an epoxy/acrylic decorative and protective exterior paint used over UltraFlex, Santa Fe Spanish Texture, Santa Fe Smooth, Santa Fe Sand Finish, and field mixed finished.

Uses:

StuccoKote is an exterior acrylic paint designed for use over high pH surfaces such as stucco, prepared masonry or concrete, and has excellent adhesion to primed metal and wood surfaces.

Color:

White (a wide variety of colors is available upon request)

Packaging:

5 gallon plastic pail- 50 lbs. (22.6 kg.)

Coverage:

Approximate coverage is 500-750 sq. ft. per pail @ 4 mils. dry thickness (coverage will vary depending on substrate, surface texture and application technique).

Mixing:

Mix with drill mixer for 1 minute, or until consistent, prior to use. Up to 16 oz of potable water may be added to adjust the workability.

Adhesion:

Excellent bonding to almost any surface except certain plastics, rubber metal and mastics. Glossy surfaces should be sanded prior to application.

Limitations:

StuccoKote exterior acrylic paint should be applied when surface and ambient conditions are between 45°F and 100°F.

Surface Preparation:

Surface must be clean and free from bond-inhibiting materials such as dirt, dust, Rust, grease, oil, efflorescence, mildew, fungus, form release agents, or any other contaminants. Remove and repair any loose mortar, stucco, concrete, or masonry by water blasting, sand blasting, scraping, or using a wire brush. Substrates shall be sound and securely fastened. Failure to correctly prepare the surface may result in product failure.

Application:

StuccoKote exterior acrylic paint may be applied by roller, brush or spray equipment. Always apply StuccoKote in a continuous application, working to a wet edge to eliminate cold joints.

Curing/Drying:

Drying time will vary depending on ambient temperature, humidity and film thickness. StuccoKote will dry completely within 12-24 hours.

Storage:

Product is good for one year when keep from freezing. Keep out of direct sunlight for prolonged periods. Do not store at temperatures above 90°F or below 40°F.

Clean Up:

Clean tools and equipment with water immediately after use.

UltraKote Products, Inc.

327 S. 27th Avenue
Phoenix, AZ 85009
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

StuccoKote

Product Data Sheet

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the StuccoKote Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc
