



# UltraKote L5

Acrylic High Build Basecoat and Finish



*UltraKote L5 is a lightweight, water-based, acrylic, high build, tintable, leveler, and finish plaster. It can be knife, trowel, sprayed, or roller applied.*

## Product Specifications:

### Packaging:

5 gallon plastic pail—50 lbs. (22.6Kg)  
1 gallon plastic pail—10 lbs. (4.52Kg)

### Coverage:

New “Level 3-4” drywall or plaster basecoats: 60-65 sq ft per gallon (two coats)

Painted drywall texture: 70-80 sq ft per gallon (two coats)

### Color:

12 Standard colors

*Custom colors available upon request.*

### Storage:

Store in a cool, dry interior place. Keep from freezing, out of direct sunlight for long periods, and at no time expose to moisture, rain or snow. Storage temperature ranges between 40°F (4.4°C) and 95°F (35°C)

### Clean up:

Clean tools and equipment with water immediately after use.

### Shelf Life:

1 year

## Uses:

Use **UltraKote L5** as a finish or over existing painted textured surfaces and new construction. **UltraKote L5** may also be used as a tintable high performance leveler in preparation for paint or smooth wall.



## Benefits:

- 100% Dust Free
- Tintable
- Durable
- No sanding required
- Excellent yield, cost effective
- Minimal surface preparation
- Knife, sprayed, trowel, or rolled
- Easily repairable

UltraKote Products  
327 South 27th Avenue, Phoenix, Arizona 85009  
Phone: 800.224.2344 Fax: 602.272.6445

[www.ultrakoteproducts.com](http://www.ultrakoteproducts.com)



# UltraKote L5

Acrylic High Build Basecoat and Finish

Decorative Finish

## Surface Preparation:

Substrate must be clean, dry, sound and free of contaminants, oil, mildew and efflorescence. Ambient conditions, substrate and the product itself must be at above 40 °F and rising during application.

## Mixing:

A small amount of clean potable water may be added to adjust consistency. Always mix UltraKote L5 prior to addition of any water.

## Application:

### New Drywall:

Using standard drywall taping products and techniques bring the wall to a Level 3-4 drywall finish. Make sure the wall has been thoroughly cleaned of any drywall dust on the surface. Next, apply a full coverage coat of **UltraKote L5** over the entire surface area. Allow first coat to dry before proceeding. Apply a second, thinner coat over the entire surface. After this coat has dried to the touch (approximately 20 minutes) it can be polished using a clean, finishing knife or dry stainless steel trowel.

### Painted Drywall Texture:

Verify that the painted surface is clean, well bonded, free of any delamination, or any bond inhibiting materials. Apply a full coverage coat of **UltraKote L5** over the entire surface. Depending on the depth of the texture, a second coat may be required to bring the surface to a good smooth wall standard. Once a smooth surface is achieved and dry to the touch (approximately 20-40 minutes), the surface can be polished with a dry stainless steel finishing knife or trowel.

### When Used as a Primer/Leveler:

Allow **UltraKote L5** to dry for a minimum of 24 hours before painting or applying any other finish over the surface. Substrate absorption, temperature and humidity affect drying time. Water-based paints are recommended. Consult the manufacturer for recommendations on using other types of paint over **UltraKote L5**.

UltraKote L5 may also be used as a leveling or resurfacing product over painted concrete tilt-up walls.

## Curing / Drying:

Drying time averages 3 hours depending on ambient temperature, humidity, and film thickness. **UltraKote L5** will dry completely within 12-24 hours.

## Limitations:

**UltraKote L5** should be applied when surface and ambient air conditions are between 40°F (4.44°C) and 95°F (35°C).

## Technical Data:

Surface Burning ASTM E 84 (Class A)	Flame Spread Index: 20 Smoke Developed Index: 5
Mildew/Mold Resistance ASTM D 3273	9-10
Water Vapor Transmission ASTM D 1653	23.9 perms
VOC (g/L)	> 20 g/l



## Precautions:

KEEP OUT OF THE REACH OF CHILDREN.  
Not for internal consumption.  
Do not apply in non-ventilated area.  
Use protective equipment such as gloves, eye protection and clothing.

## First Aid:

In case of eye contact, flush with water at least 15 minutes.  
In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing.  
If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.  
For additional information refer to the Material Safety Data Sheet (MSDS).

## Disposal:

Dispose of in accordance with local, state or federal regulations.

## Warning:

KEEP OUT OF REACH OF CHILDREN.  
NOT FOR INTERNAL CONSUMPTION,  
FOR INDUSTRIAL USE ONLY

## Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

## Prop 65:

This product contains materials listed by the state of California known to cause cancer, birth defects, or other reproductive harm.

## Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Information Guide conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most current information, contact UltraKote Products or visit website at [www.ultrakoteproducts.com](http://www.ultrakoteproducts.com).

January 2012

UltraKote Products  
327 South 27th Avenue, Phoenix, Arizona 85009  
Phone: 800.224.2344 Fax: 602.272.6445

[www.ultrakoteproducts.com](http://www.ultrakoteproducts.com)

