

**Description:**

DuraTex is a premium, integrally colored acrylic synthetic stucco for use over UltraKote 1, UltraKote Pre-Mix, Santa Fe base, Traditional Stucco Cement, SkimKote, FoamKote or other approved base coats. DuraTex is ready mixed aggregated product available in multiple textures, giving the ability to achieve numerous appearances.

Uses:

DuraTex may be used for interior or exterior applications over either cementitious and non-cementitious base coats, and prepared: concrete masonry, drywall, painted surfaces, and synthetic stucco. DuraTex has excellent adhesion properties and can assist in efflorescence resistance when surfaces are pretreated with stucco conditioner.

Color:

All UltraKote standard colors. Custom colors upon request.

Packaging:

65lb. (29.48 Kg) plastic pail.

Vapor Permeability:

DuraTex is impermeable to water in liquid form but breathable to water vapor.

Adhesion

DuraTex offers excellent bond strength to most porous/absorptive surface. Glossy

surfaces should be sanded prior to application.

Coverage:

Approximate coverage is 100 to 150 f² per pail @ 10 mils. dry thickness. Coverage will vary depending on substrate, surface texture and application technique.

Mixing:

Mix with a drill mixer (1 to 2 minutes) until consistency is achieved. Up to 12 oz. Of potable water may be added to assist in achieving the desired consistency. Avoid over mixing or air-entraining the finish.

Limitations:

DuraTex exterior acrylic paint should be applied when surface and ambient conditions are between 45°F (7/22°C) and 110°F. (43.33°C). DuraTex should be protected from rain for 24 hours. Substrate must have a pH of 12 or lower.

Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water blasting, sand blasting, scraping or using a wire brush. Repair all cracks with UltraPatching Compound. If applying over a painted

surface, test paint to make sure it is load bearing. Failure to correctly prepare the surface may result in product failure.

Application:

DuraTex should be applied with a stainless steel trowel or approved spray equipment. Always apply DuraTex in a continuous application, working to a wet edge to eliminate cold joints. Float the finish with a hard plastic float using a "figure 8" pattern. Details may be finished with a slightly dampened sponge float. Avoid water drops or runs on freshly floated Finish.

Curing / Drying:

Drying time averages 4 hours, depending on ambient temperature, wind and humidity. DuraTex will fully cure in two weeks.

Storage/Shelf Life:

One year when stored in a cool dry location and out of direct sunlight. Keep from freezing.

Clean Up:

Clean tools and equipment with water immediately after use.

UltraKote Products, Inc.

327 S. 27th Avenue
Phoenix, AZ 85009
Phone: (602) 272-5830 • (800) 224-2344

DuraTex

Product Data Sheet

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the DuraTex Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc
