



Santa Fe Smooth Finish

Product Data Sheet

Description:

Santa Fe Smooth Finish is a proprietary mixture of Portland Cement, hydrated lime, silica sand and proprietary additives. Santa Fe Smooth Finish will provide a lower pH than a field mix finish.

Uses:

Santa Fe Smooth Finish is a Premium ready-mixed smooth finish texture material for use over UltraKote, Santa Fe Base or Traditional Stucco Cement. Santa Fe Smooth Finish can also be used over SkimKote if modified with Ultra Admix. Santa Fe Smooth Finish is not recommended as a finished product and should be covered with StuccoKote, DuraKote or StretchKote. UltraAdmix is recommended to reduce efflorescence, water penetration, cracking, and to increase flexural strength. UltraAdmix will also increase the life of the product in geographic regions where freeze/thaw cycles routinely occurs over prolonged periods.

Color:

Off White
White (special order only)

Packaging:

90 lb.(40. Kg) multi-wall paper sack

Coverage :

Approximate coverage is 90 f² at 1/8" thick. Coverage will vary depending on application techniques, substrate and temperature conditions.

Mixing:

To begin, place 1 to 1.5 gallons of potable water into a mechanical mixer. As the mixer is running add one 90 lb. bag of Santa Fe Smooth Finish. Gradually add the remaining .5 to 1 gallons of potable water and blend until the desired consistency is achieved (about 4 to 5 minutes). Stop the mixing and allow the material to slake for 3 to 4 minutes. Then start the mixing again to break the initial set (usually 1 to 2 minutes). Working time per batch is 45 minutes or less. **NOTE:** *The amount of water needed to reach the desired workability will vary with temperature, humidity, wind, exposure, and site location or region.*

Limitations:

Santa Fe Smooth Finish should be applied when surface and ambient temperatures are between 40° f (4.44°C) and 110° F (43.33°C) during application and cure time. Santa Fe Smooth Finish is not recommended for use over painted surfaces or stucco accessories. Weather conditions will effect drying time and workability.

Surface Preparation:

Surface must be clean and free

of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose mortar, stucco, concrete, or masonry by water blasting, sand blasting, scraping, or using a wire brush. Repair all cracks with a patching compound and prime the entire surface prior to application to avoid telegraphing lines through the dried finish.

Application:

Santa Fe Smooth Finish should be applied 2 to 3 days after the initial application of Santa Fe Base, UltraKote one coat, or the second coat of UltraKote Traditional Stucco Cement. Santa Fe Smooth Finish should be applied in two coats, using the "double back" method, to a thickness of 1/16" to 1/8". Always work to a wet edge to avoid cold joints. Never apply Santa Fe Smooth Finish to frozen substrates or substrates with frost.

Curing/Drying:

Santa Fe Smooth Finish must be kept moist for at least 48 hours. Start light fogging after the initial set (1 to 2 hours). Finish should cure completely within 28 days.

Shelf Life:

One year when stored in a cool dry location out of direct sunlight.

Clean Up:

Clean tools and equipment with

UltraKote Products, Inc.

327 S. 27th Avenue
Phoenix, AZ 85009
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

Santa Fe Smooth Finish

Product Data Sheet

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the Santa Fe Smooth Finish Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc
