



# UltraFinish

## Product Data Sheet

---

### Description:

UltraFinish is an integrally colored elastomeric finish for use over UltraKote one coat stucco, Santa Fe Base, Traditional Stucco Cement, and other approved base coats. UltraFinish is a ready-mixed aggregated product available in multiple textures and colors for maximum design flexibility.

### Uses:

Ultra Finish may be used for interior or exterior applications over cementitious surfaces such as prepared concrete and masonry or non-cementitious surfaces such as prepared drywall, painted surfaces, or synthetic stucco. UltraFinish has excellent adhesion properties and can assist in efflorescence resistance when surfaces are prepared with Stucco Conditioner.

### Color:

All UltraKote Standard colors with custom colors on request.

### Packaging:

65 lb (29.48 Kg) plastic pail.

### Vapor permeability :

UltraFinish is impermeable to water in liquid form but breathable to water vapor.

### Adhesion:

UltraFinish offers excellent bond strength to most porous or absorptive surfaces. Glossy or smooth surfaces should be sanded prior to application.

### Coverage:

100 to 150 ft<sup>2</sup> (9.2 -13.8 m<sup>2</sup>) depending on surface condition and preparation, application methods, and texture desired.

### Mixing:

Prior to use add all the pigment from the color tint pack into the pail and mix to an even consistency. The time required is usually less than 2 minutes at relatively low RPM's to avoid over mixing or air-entraining the material. A small amount of water (12 oz or less) can be added to adjust the consistency.

### Limitations:

UltraFinish should be applied when surface and ambient temperatures are between 45° F (7.22°C) and 110° F (43.33°C) during application and cure time. UltraFinish should be protected from rain for a minimum of four days after application.

### Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose mortar, stucco, concrete, or masonry by water blasting, sand blasting, scraping, or using a wire brush. Repair all cracks with a patching compound and prime the entire surface prior to the Finish application to avoid telegraphing lines through the dried finish.

### Application:

UltraFinish should be applied with a stainless steel trowel or approved spray equipment. Generally the finish application requires two people per scaffold stage, one applying and one floating. Always apply UltraFinish in a continuous application working to a wet edge to eliminate cold joints. Using a hard plastic float, float the finish in a "figure 8". Details or plant-ons may be finished with a slightly dampened sponge float. Always avoid excess water drops or runs on freshly floated material.

### Curing/Drying:

Drying time averages about 4 hours depending on ambient temperatures, surface temperatures, wind, and humidity. UltraFinish should be protected from rain and moisture for a minimum of 4 days. UltraFinish usually cures fully within two weeks.

### Shelf Life:

One year when stored in a cool dry location out of direct sunlight and kept from freezing.

### Clean Up:

Clean tools and equipment with water immediately after use.

---

### UltraKote Products, Inc.

327 S. 27th Avenue  
Phoenix, AZ 85009  
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

# UltraFinish

## Product Data Sheet

---

**Precautions:**

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

**First Aid:**

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the UltraFinish Material Safety Data Sheet (MSDS).

**Disposal:**

Dispose of in accordance with local, state or federal regulations.

**Warning:**

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

**Spills:**

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

**Prop 65:**

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

**Technical Support:**

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc

---