



# UltraGrey Finish

## Product Data Sheet

### Description:

UltraGrey Finish is an elastomeric finish for use over UltraKote one-coat stucco, Santa Fe Base, Traditional Stucco Cement, SkimKote, FoamKote and other approved base coats. UltraGrey is a ready-mixed aggregated product and is available in multiple sand textures for maximum design flexibility.

### Uses:

UltraGrey Finish may be used for exterior applications over cementitious or non-cementitious and prepared concrete or masonry. UltraGrey Finish has excellent adhesion properties and can assist in efflorescence resistance when surfaces are pretreated with Stucco Conditioner.

### Color:

Gray

### Packaging:

65lb Pail (29.48 Kg)  
51lb Box. (23.13 Kg)

### Vapor permeability:

UltraGrey Finish is impermeable to water in liquid form but breathable to water vapor.

### Adhesion:

UltraGrey Finish offers excellent bond strength to most porous or absorptive surfaces. Glossy or smooth surfaces should be sanded prior to application.

### Coverage:

75-150 f<sup>2</sup> depending on surfaces conditions, surface preparations, application methods, and texture desired.

### Mixing:

Remove the bladder from the box and empty into a 5 gal. Pail. Blend the contents until consistent. The time required is generally about 1 minute at a low rpm. A small amount of water (6 to 8 oz) may be added to enhance the workability. Avoid over-mixing or air-entraining the material.

### Limitations:

UltraGrey Finish should be applied when surface and ambient temperatures are between 45° F (7.22° C) and 110° F (43.33° C) during application. UltraGrey Finish should be protected from rain for a minimum of four days after application.

### Surface Preparation:

Surface must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete, or masonry by water blasting, sand blasting, scraping, or using a wire brush. Repair large cracks with a patching compound telegraphing lines through the dried finish.

### Application:

UltraGrey Finish should be applied with a stainless steel trowel. Always apply UltraGrey Finish in a continuous application working to a wet edge to eliminate cold joints. Float the UltraGrey Finish with either a green sponge float or a hard plastic float using a light brushing or dragging motion to open the sand texture. Avoid applying excessive pressure. Detail areas may be finished with a lightly dampened sponge float. Avoid excess water drops or runs on freshly floated material.

UltraGrey Finish may be painted when dry, approximately 24 hours depending on the ambient and surface temperature conditions.

### Curing/Drying:

Drying time averages four hours, depending on ambient temperature, surface temperature and humidity. UltraGrey Finish should be protected from rain and moisture for a minimum of 4 days and it cures fully within two weeks.

### Shelf Life:

One year when stored in a cool dry location out of direct sunlight and kept from freezing.

### Clean Up:

Clean tools and equipment with water immediately after use.

### UltraKote Products, Inc.

327 S. 27th Avenue  
Phoenix, AZ 85009  
Phone: (602) 272-5830 • (800) 224-2344

Last Revised : March 2006

# UltraGrey Finish

## Product Data Sheet

---

**Precautions:**

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

**First Aid:**

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the UltraGrey Finish Material Safety Data Sheet (MSDS).

**Disposal:**

Dispose of in accordance with local, state or federal regulations.

**Warning:**

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

**Spills:**

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

**Prop 65:**

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

**Technical Support:**

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc

---