

Description:

UltraPrime™ is a premium acrylic protective exterior primer. UltraPrime™ can be used to protect most exterior surfaces including stem and foundation walls, stucco, EIFS.

Uses:

UltraPrime™ is designed to be used over high pH cementitious surfaces such as stucco, tilt-up concrete, prepared masonry and brick.

Color:

White

(Can be tinted to match all colors in the UltraKote™ Fan Deck - custom colors are available upon request).

Packaging:

5 gallon plastic pail 52 lbs.
(22.6kg.)

Coverage:

Approximate coverages are as follows:

- 52 lbs. UltraPrime™ over stucco = 250 ft.²
- 52 lbs. UltraPrime™ over concrete masonry = 150 ft.²

(coverage will vary depending on texture, substrate and suction)

Vapor Permeability:

UltraPrime™ is impermeable to water in liquid form, but breathable to water vapor.

Mixing:

Prior to use mix with a drill motor and mixing paddle for ab out one minute. Do not over mix or air-entrained the material which will decrease bonding characteristics. Up to 16 ounces of clean potable water may be added to UltraPrime™ to aid in spray application.

Limitations:

Use UltraPrime™ when surface and ambient conditions are above 40°F and below 100°F during application and cure time. Substrate should have a pH level of 12 or lower. UltraPrime™ is not recommended for use on frozen substrates. Finish color is very consistent but may vary slightly depending on suction, drying time, application technique and ambient conditions. UltraPrime™ should be protected from rain for a minimum of 24 hours (if curing at low temperatures, protect for 2 days).

Surface Preparation:

Surfaces must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Remove and repair any loose paint, mortar, stucco, concrete or masonry by water-blasting, sand-blasting, scraping or using a wire brush. Substrate should be securely fastened. Repair all cracks with appropriate

patching compound. Mask off area accordingly. Failure to prepare the surface correctly may result in product failure.

Application:

UltraPrime™ exterior acrylic paint may be applied with brush, roller or approved spray equipment. If rolling apply evenly not allowing roller marks. Apply finish coat after prime coat has fully dried. If spraying material, spray in a side to side or up and down pattern. Always apply UltraPrime™ in continuous application, working to a wet edge to avoid cold joints. Avoid water drops and runs on uncured material.

Shelf Life:

One year when stored in a cool dry location. Keep out of direct sunlight and protect from freezing.

Curing/Drying:

UltraPrime™ will set in between 5 to 30 minutes, dry to touch in 1-4 hours and will be fully cured in 14 days.

Clean Up:

Clean tools and equipment with water immediately after use.

UltraPrime

Product Data Sheet

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the UltraPrime Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-272-5830. Information contained in this Product Data Sheet conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc
